

■ Brushcutter VB 260 L



- Forged steel crankshaft and connecting rod for long life and unwavering performance over time.
- Starter housing and nose cone in aluminium for maximum strength, even when tackling heavy workloads.
- Equipped with generously proportioned clutch giving improved control of the machine (tool stays motionless at idling speed), increased protection to the engine, and better results when cutting long grass.
- Flywheel with large fins designed to provide optimum cooling, even in high ambient temperatures.
- Self-lubricating sheath protecting the transmission and guaranteeing fewer vibrations, for increased working comfort.
- Carburettor filled by primer with fuel mixture to ensure easy starting with a limited number of pulls, even after lengthy periods of inactivity.
- Tap 'n Go head fitted as standard: no disruption of work, with line feed induced automatically by tapping the head on the ground.
- Superior quality anti-vibration system with 5 self-lubricating bushes along the bore of the shaft arm tube and 1 anti-vibration mount at the aluminium nose cone, for maximum operating comfort.
- Easy access to air filter, with no tools needed, ensuring maximum convenience for cleaning and maintenance purposes.

■ Brushcutter VB 260 L



TECHNICAL SPECIFICATIONS

Engine	EMAK - 2-stroke
Power / Displacement	1.0 HP - 0.8 kW / 25.4 cm ³
Fuel tank capacity	0.75 L
Transmission / Tube diameter	rigid / 26 mm
Handle	single
Anti-vibration system	1 mount on nose cone + 5 self-lubricating bushes in tube
Clutch	yes
Weight	5.6 Kg
Standard cutting tools	Tap'n go" head Ø 130 mm, Ø 2.4 mm line
Cutting diameter	38 cm
Harness	single

PRODUCT DATA

Product Code	61319001E2
Dimensions, single pack (cm)	183 x 22 x 30
Quality / Dimensions, pallet (cm)	50 / 183 x 108 x 128 (30 pz) 183 x 108 x 88 (20 pz)
Quality / Truck, 1360 cm	700
Quality / 40' ctr, palletized	600
EAN Code	8026619022693

QUALITY MARKS

